



N100 PORT SYSTEM FOR Canon RF-S CAMERA SYSTEM (RF-S & EF-Mount Format Lens)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
STANDARD ZOOM APSC	Canon RF-S 18-45mm f4.5-6.3 IS STM	19596 CR1845-Z			37181 N100 Flat Port 50	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.8X Working Distance 44-81mm
							81302 CMC - 2	Max. Magnification 0.6X Working Distance 68-140mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Max. Magnification 0.8X Working Distance 44-81mm
							81302 CMC - 2	Max. Magnification 0.6X Working Distance 68-140mm
						83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83201 WWL - 1	Lens FOV 75-35° Converted FOV 130-60° Zoom Range 18-45mm
							83202 WWL - 1B	Lens FOV 75-35° Converted FOV 130-60° Zoom Range 18-45mm
							83203 * WWL - C	Lens FOV 75-35° Converted FOV 116-52° Zoom Range 18-45mm
							86201 MWL - 1	Lens FOV 40-35° Converted FOV 150-130° Zoom Range 38-45mm
				37402 N100 Extension Ring 40				Lens FOV 75-35° Converted FOV 130-60°
					85203 N100 WACP-1			Lens FOV 75-35° Converted FOV 130-60°
					85205 N100 WACP - C			Lens FOV 75-35° Converted FOV 130-60°
			37305 N100 to N120 35.5mm Port Adaptor II		85201 N120 WACP - 1			Lens FOV 75-35° Converted FOV 130-60°
CANON EF-MOUNT	Canon EF-mount Lenses with Canon Mount Adaptor EF-EOS R <i>* Canon control ring and Drop-in filter mount adaptors are not supported by these setups</i>		37305 N100 to N120 35.5mm Port Adaptor II					N120 Canon EF-Mount Port System
	Canon RF mount Fullframe Lenses		37305 N100 to N120 35.5mm Port Adaptor II					N120 Canon RF-Mount Port System

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended port system based on best optical performance
* Secondary setup recommendation based on optical performance