



## N100 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM ( Full Frame Format Lens )

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
MACRO FULL FRAME	Sony SEL50M18 FE 50mm f/1.8				On Full Frame Sensor	<b>37123</b> N100 Macro Port 55			
					With Crop/APS-C Format	<b>37123</b> N100 Macro Port 55	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81301</b> CMC - 1	Max. Magnification 0.9X Working Distance 60-77mm
	<i>* These setups are only recommended to use with Crop/APS-C format enabled to avoid vignetting</i>								
							SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81301</b> CMC - 1	Max. Magnification 0.9X Working Distance 60-77mm
							<b>81302</b> CMC - 2	Max. Magnification 0.6X Working Distance 37-48mm	
							<b>81302</b> CMC - 2	Max. Magnification 0.6X Working Distance 37-48mm	
							<b>83250</b> M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	<b>86201</b> MWL - 1	Lens FOV 31° Converted FOV 116°
		Sony SEL50M28 FE 50mm f/2.8 Macro			<b>37402</b> N100 Extension Ring 40	<b>37127</b> N100 Flat Port 32			
		Sony SEL55F18Z AE Sonnar T* FE 55mm F1.8 ZA				<b>37123</b> N100 Macro Port 55			<i>* This setup is not compatible with Extension Rings I SN:A175724 before 09/2016</i>
		Sony SEL90M28G FE 90mm f/2.8 Macro G OSS	<b>37147</b> SE90-F			<b>37126</b> N100 Macro Port 105	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81201</b> SMC - 1	Max. Magnification 2.2X Working Distance 45-93mm
							SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81201</b> SMC - 1	Max. Magnification 2.2X Working Distance 45-93mm
							<b>81202</b> SMC - 2	Max. Magnification 3.4X Working Distance 22-36mm	
						<b>81202</b> SMC - 2	Max. Magnification 3.4X Working Distance 22-36mm		
						<b>83250</b> M67 to Bayonet Mount Converter II	<b>87303</b> EMWL Set#3	Lens FOV 27° Converted FOV 60°/100°/130°/160°	
	Sigma 105mm F2.8 DG DN Macro Art	<b>37166</b> SGE105-F			<b>37125</b> N100 Macro Port 110	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81201</b> SMC - 1	Max. Magnification 2.3X Working Distance 49-80mm	
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81201</b> SMC - 1	Max. Magnification 2.3X Working Distance 49-80mm	
						<b>81202</b> SMC - 2	Max. Magnification 3.6X Working Distance 26-35mm		
						<b>81202</b> SMC - 2	Max. Magnification 3.6X Working Distance 26-35mm		
						SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81201</b> SMC - 1	Max. Magnification 2.3X Working Distance 49-80mm	
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81201</b> SMC - 1	Max. Magnification 2.3X Working Distance 49-80mm	
						<b>81202</b> SMC - 2	Max. Magnification 3.6X Working Distance 26-35mm		
						<b>81202</b> SMC - 2	Max. Magnification 3.6X Working Distance 26-35mm		
						SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81201</b> SMC - 1	Max. Magnification 2.3X Working Distance 49-80mm	
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81201</b> SMC - 1	Max. Magnification 2.3X Working Distance 49-80mm	
						<b>81202</b> SMC - 2	Max. Magnification 3.6X Working Distance 26-35mm		
						<b>81202</b> SMC - 2	Max. Magnification 3.6X Working Distance 26-35mm		
						SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	<b>81201</b> SMC - 1	Max. Magnification 2.3X Working Distance 49-80mm	
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	<b>81201</b> SMC - 1	Max. Magnification 2.3X Working Distance 49-80mm	
						<b>81202</b> SMC - 2	Max. Magnification 3.6X Working Distance 26-35mm		
						<b>81202</b> SMC - 2	Max. Magnification 3.6X Working Distance 26-35mm		

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance

\* Secondary setup recommendation based on optical performance



## N100 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM ( Full Frame Format Lens )

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
<b>MACRO</b> FULL FRAME	Laowa 24mm f/14 2X Macro Probe	19155 N120 DSLR Gear Set	<sup>1</sup> 37305 N100 to N120 35.5mm Port Adaptor II	22170 + 22171 N120 Extension Ring 70 II + Focus Knob	16336 N120 Port Adaptor			
	Sony FE 20-70mm f/4 G	37174 SFE2070-Z	<sup>1</sup> 37305 N100 to N120 35.5mm Port Adaptor II	<ul style="list-style-type: none"> <li>22120 N120 Extension Ring 20 II</li> <li>22135 N120 Extension Ring 35 II</li> <li>22140 N120 Extension Ring 40 II</li> </ul>	<ul style="list-style-type: none"> <li>85204 N120 WACP - 2</li> <li>85201 / 85206 N120 WACP - 1 / WACP - 1B</li> <li>18809 180mm Optical Glass Wide Angle Port</li> <li>18802 8.5" Acrylic dome port</li> <li>18812 230mm Optical Glass Wide Angle Port</li> <li>* 18815 250mm Optical Glass Wide Angle Port</li> </ul>		<ul style="list-style-type: none"> <li>* slight vignetting at 20mm in RAW format</li> </ul>	<ul style="list-style-type: none"> <li>Lens FOV 94-59°</li> <li>Converted FOV 116-73°</li> <li>Zoom Range 20-38mm</li> <li>Lens FOV 75-71°</li> <li>Converted FOV 130-123°</li> <li>Zoom Range 28-30mm</li> </ul>
<b>STANDARD ZOOM</b> FULL FRAME	Sony SEL2470Z Vario-Tessar T* FE 24-70mm F4 ZA OSS	<ul style="list-style-type: none"> <li>37149 SE2470-Z</li> <li>37149 + 37148 SE2470-Z + SE2470-F</li> </ul>	<sup>1</sup> 37305 N100 to N120 35.5mm Port Adaptor II	<ul style="list-style-type: none"> <li>22130 N120 Extension Ring 30 II</li> </ul>	<ul style="list-style-type: none"> <li>85204 N120 WACP - 2</li> <li>18809 180mm Optical Glass Wide Angle Port</li> </ul>			<ul style="list-style-type: none"> <li>Lens FOV 84-34°</li> <li>Converted FOV 98-72°</li> <li>Zoom Range 24-35mm</li> </ul>
	Sony SEL2470GM FE 24-70mm f/2.8 GM	<ul style="list-style-type: none"> <li>37151 SFE2470GM-Z</li> <li>37151 + 37152 SFE2470GM-Z +</li> </ul>	<sup>1</sup> 37305 N100 to N120 35.5mm Port Adaptor II	<ul style="list-style-type: none"> <li>22130 N120 Extension Ring 30 II</li> <li>22160 N120 Extension Ring 60 II</li> </ul>	<ul style="list-style-type: none"> <li>85204 N120 WACP - 2</li> <li>18809 180mm Optical Glass Wide Angle Port</li> </ul>			<ul style="list-style-type: none"> <li>Lens FOV 84-34°</li> <li>Converted FOV 98-72°</li> <li>Zoom Range 24-35mm</li> </ul>
	Sony SEL2470GM2 FE 24-70mm f/2.8 GM II	37173 SFE2470II-Z	<sup>1</sup> 37305 N100 to N120 35.5mm Port Adaptor II	<ul style="list-style-type: none"> <li>22150 N120 Extension Ring 50 II</li> <li>22155 N120 Extension Ring 55 II</li> </ul>	<ul style="list-style-type: none"> <li>18802 8.5" Acrylic dome port</li> <li>18812 230mm Optical Glass Wide Angle Port</li> <li>* 18815 250mm Optical Glass Wide Angle Port</li> <li>18809 180mm Optical Glass Wide Angle Port</li> </ul>			
	Sony SEL28F20 FE 28mm f/2	37150 SE28-F		<ul style="list-style-type: none"> <li>37401 N100 Extension Ring 30</li> </ul>	<ul style="list-style-type: none"> <li>37127 N100 Flat Port 32</li> <li>85205 N100 WACP - C</li> <li>* 85203 / 85206 N100 WACP-1 / WACP-1B</li> </ul>	83250 M67 to Bayonet Mount Converter II	83202 WWL - 1B	<ul style="list-style-type: none"> <li>Lens FOV 75°</li> <li>Converted FOV 130°</li> <li>Lens FOV 75°</li> <li>Converted FOV 130°</li> <li>Lens FOV 75°</li> <li>Converted FOV 130°</li> </ul>

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance. Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance

\* Secondary setup recommendation based on optical performance



## N100 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM ( Full Frame Format Lens )

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE			
STANDARD ZOOM FULL FRAME	Sony SEL2860 FE 28-60mm F4-5.6	37163 SFE2860-Z		37401 + 37401 N100 Extension Ring 30 + N100 Extension Ring 30	37129 N100 180mm Optical Glass Wide Angle Port			Lens FOV 75-40° Converted FOV 130-69°			
				37401 N100 Extension Ring 30	* 85203 / 85206 N100 WACP-1 / WACP-1B			Lens FOV 75-40° Converted FOV 130-69°			
					85205 N100 WACP - C			Lens FOV 75-40° Converted FOV 130-69°			
				<sup>1</sup> 37305 N100 to N120 35.5mm Port Adaptor II	22130 N120 Extension Ring 30 II			* 18809 180mm Optical Glass Wide Angle Port			
				37163 + 37168 SFE2860-Z + SFE2860-F (WACP-1)	<sup>1</sup> 37305 N100 to N120 35.5mm Port Adaptor II			85201 / 85206 N120 WACP - 1 / WACP - 1B	Lens FOV 75-39° Converted FOV 130-68°		
				37163 + 37164 SFE2860-Z + SFE2860-F				37165 N100 Flat Port 45 with Focus Knob			
	Sony SEL2870 FE 28-70mm F3.5-5.6 OSS	37141 SE2870-Z		37403 N100 Extension Ring 50	* 85203 / 85206 N100 WACP-1 / WACP-1B				Lens FOV 75-34° Converted FOV 130-59°		
					85205 N100 WACP - C				Lens FOV 75-34° Converted FOV 130-59°		
					37124 Flat port 66 with M77 Thread				83251 M77 to Bayonet Mount Converter II	86201 MWL - 1	Lens FOV 39-34° Converted FOV 150-110° Zoom Range 60-70mm
				37141 + 37167 SE2870-Z + SE2870-F	<sup>1</sup> 37305 N100 to N120 35.5mm Port Adaptor II				22120 N120 Extension Ring 20 II	85201 / 85206 N120 WACP - 1 / WACP - 1B	Lens FOV 75-34° Converted FOV 130-59°
									37122 4" Wide angle port		
									* 37130 N100 Flat port 23	83250 M67 to Bayonet Mount Converter II	<sup>1</sup> 83201 WWL - 1
Sony SEL35F28Z Sonnar T* FE 35mm F2.8 ZA								<sup>1</sup> 83202 WWL - 1B	Lens FOV 62° Converted FOV 109°		
Sigma 24-70mm f/2.8 DG DN Art	37171 SSF2470-Z		<sup>1</sup> 37305 N100 to N120 35.5mm Port Adaptor II	22155 N120 Extension Ring 55 II	18802 8.5" Acrylic dome port						
					18809 180mm Optical Glass Wide Angle Port						
					* 18812 230mm Optical Glass Wide Angle Port						

\* Please refer to the following page for more setup options

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.  
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.  
Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance  
\* Secondary setup recommendation based on optical performance



## N100 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM ( Full Frame Format Lens )

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	OPTICAL PERFORMANCE
STANDARD ZOOM FULL FRAME	Sigma 24-70mm f/2.8 DG DN Art	37171 SSF2470-Z	1 37305 N100 to N120 35.5mm Port Adaptor II	22120 N120 Extension Ring 20 II	* 85204 N120 WACP - 2	Lens FOV 84-64° Converted FOV 98-74° Zoom Range 24-34mm
	Tamron 28-75mm f/2.8 Di III RXD	37159 STE2875-Z  37159 + 37160 STE2875-Z + STE2875-F	1 37305 N100 to N120 35.5mm Port Adaptor II	22140 N120 Extension Ring 40 II  22135 N120 Extension Ring 35 II  22150 N120 Extension Ring 50 II	85201 / 85206 N120 WACP - 1 / WACP - 1B  85201 / 85206 N120 WACP - 1 / WACP - 1B  18802 8.5" Acrylic dome port 18809 180mm Optical Glass Wide Angle Port * 18812 230mm Optical Glass Wide Angle Port	Lens FOV 73° Converted FOV 127° Zoom Range 29mm  Lens FOV 75-52° Converted FOV 130-90° Zoom Range 28-45mm
WIDE ANGLE FULL FRAME	Sony SEL1224GM FE 12-24mm F2.8 GM	37161 SFE1224GM-Z  37161 + 37162 SFE1224GM-Z + SFE1224GM-F	1 37305 N100 to N120 35.5mm Port Adaptor II	22155 N120 Extension Ring 55 II	18812 230mm Optical Glass Wide Angle Port	* This setup is not compatible with Extension Rings I SN:A055053 before 09/2016
	Sony SEL1224G FE 12-24mm F4 G	37153 SFE1224-Z  37153 + 37154 SFE1224-Z + SFE1224-F	1 37305 N100 to N120 35.5mm Port Adaptor II	22140 N120 Extension Ring 40 II	18812 230mm Optical Glass Wide Angle Port	
	Sony FE 14mm f/1.8 GM		1 37305 N100 to N120 35.5mm Port Adaptor II	22120 N120 Extension Ring 20 II  22130 N120 Extension Ring 30 II	18809 180mm Optical Glass Wide Angle Port  18802 8.5" Acrylic dome port * 18812 230mm Optical Glass Wide Angle Port 18815 250mm Optical Glass Wide Angle Port	
	Sony SEL1635GM FE 16-35mm F2.8 GM	37155 SFE1635GM-Z  37155 + 37156 SFE1635GM-Z + SFE1635GM-F	1 37305 N100 to N120 35.5mm Port Adaptor II	37306 N100 to N120 25mm Port Adaptor	22130 N120 Extension Ring 30 II  22160 N120 Extension Ring 60 II  22170 N120 Extension Ring 70 II	85204 N120 WACP - 2  18809 180mm Optical Glass Wide Angle Port * 18812 230mm Optical Glass Wide Angle Port

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.  
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.  
Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance  
\* Secondary setup recommendation based on optical performance



## N100 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM ( Full Frame Format Lens )

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
WIDE ANGLE FULL FRAME	Sony SEL1635GM2 FE 16-35mm f/2.8 GM II	37175 SFE1635GMII-Z	1 37305 N100 to N120 35.5mm Port Adaptor II	21110 N120 Extension Ring 10	85204 N120 WACP - 2	* This setup is only compatible with WACP-2 before SN:A526311 * Minimum focus distance from port to subject is 0.10m at 16mm and 0.10m at 35mm		Lens FOV 107-63° Converted FOV 128-77°	
				22110 N120 Extension Ring 10 II	* 85204 N120 WACP - 2			* This setup is only compatible with WACP-2 SN:A526311 onwards * Minimum focus distance from port to subject is 0.10m at 16mm and 0.10m at 35mm	Lens FOV 107-63° Converted FOV 128-77°
				22140 N120 Extension Ring 40 II	85201 / 85206 N120 WACP - 1 / WACP - 1B		On APS-C Sensor  On Full Frame Sensor * Minimum focus distance from port to subject is 0.10m at 28mm and 0.10m at 35mm	Lens FOV 75-45° Converted FOV 130-78°  Lens FOV 75-63° Converted FOV 130-109° Zoom Range 28-35mm	
				22150 N120 Extension Ring 50 II	18809 180mm Optical Glass Wide Angle Port				
				22160 N120 Extension Ring 60 II	18802 8.5" Acrylic dome port  * 18812 230mm Optical Glass Wide Angle Port				
	Sony SEL1635Z Vario-Tessar T* FE 16-35mm F4 ZA OSS	37145 SE1635-Z  37145 + 37146 SE1635-Z + SE1635-F	1 37305 N100 to N120 35.5mm Port Adaptor II	37401 + 37403 N100 Extension Ring 30 + N100 Extension Ring 50	37129 N100 180mm Optical Glass Wide Angle Port				
				21110 N120 Extension Ring 10	85204 N120 WACP - 2	* This setup is only compatible with WACP-2 before SN:A526311		Lens FOV 107-63° Converted FOV 128-77°	
				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2	* This setup is only compatible with WACP-2 SN:A526311 onwards		Lens FOV 107-63° Converted FOV 128-77°	
				22150 N120 Extension Ring 50 II	18809 180mm Optical Glass Wide Angle Port				
				22160 N120 Extension Ring 60 II	* 18812 230mm Optical Glass Wide Angle Port				
	Sony FE PZ 16-35mm f/4 G	37172 SFE1635-Z	1 37305 N100 to N120 35.5mm Port Adaptor II	37403 N100 Extension Ring 50	37129 N100 180mm Optical Glass Wide Angle Port				
				22125 N120 Extension Ring 25 II	18802 8.5" Acrylic dome port  18812 230mm Optical Glass Wide Angle Port				
				22120 N120 Extension Ring 20 II	18809 180mm Optical Glass Wide Angle Port				
				22135 N120 Extension Ring 35 II	* 18815 250mm Optical Glass Wide Angle Port				
				21110 N120 Extension Ring 10	85201 N120 WACP - 1	* This setup is only compatible with WACP-1 before SN: A502435		Lens FOV 75-63° Converted FOV 130-109° Zoom Range 28-35mm	
22110 N120 Extension Ring 10 II				85201 N120 WACP - 1	* This setup is only compatible with WACP-1 SN: A502435 onwards		Lens FOV 75-63° Converted FOV 130-109° Zoom Range 28-35mm		

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.  
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.  
Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance  
\* Secondary setup recommendation based on optical performance



## N100 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM ( Full Frame Format Lens )

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
WIDE ANGLE FULL FRAME	Sony FE 24mm f/2.8 G				<b>37130</b> N100 Flat Port 23	<b>83250</b> M67 to Bayonet Mount Converter II	<b>83203</b> WWL-C	Lens FOV 84° Converted FOV 130°
	Sony FE 24mm f/1.4 GM		<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>22140</b> N120 Extension Ring 40 II	<b>18802</b> 8.5" Acrylic dome port  * <b>18809</b> 180mm Optical Glass Wide Angle Port			Lens FOV 84° Converted FOV 98°
	Sony FE PZ 28-135mm f/4 G OSS	<b>37169</b> SFE28135-Z  <b>37169 + 37170</b> STE28135-Z + STE28135-F	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>22190</b> N120 Extension Ring 90 II	<b>18812</b> 230mm Optical Glass Wide Angle Port			
	Sigma 14-24mm F2.8 DG DN	<b>19726</b> SLE1424-Z  <b>19726 + 19727</b> SLE1424-Z + SLE1424-F	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>22125</b> N120 Extension Ring 25 II  <b>22140</b> N120 Extension Ring 40 II  <b>22150</b> N120 Extension Ring 50 II  <b>22160</b> N120 Extension Ring 60 II	<b>85204</b> N120 WACP - 2  <b>18809</b> 180mm Optical Glass Wide Angle Port  <b>18812</b> 230mm Optical Glass Wide Angle Port  * <b>18815</b> 250mm Optical Glass Wide Angle Port  <b>18802</b> 8.5" Acrylic dome port			Lens FOV 94-84° Converted FOV 115-98° Zoom Range 20-24mm
	Sigma 24mm f/3.5 DG DN				<b>37127</b> N100 Flat Port 32	<b>83250</b> M67 to Bayonet Mount Converter II	<b>83203</b> WWL-C	Lens FOV 84° Converted FOV 130°
				<b>37403</b> N100 Extension Ring 50	* <b>37129</b> N100 180mm Optical Glass Wide Angle Port			
			<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>22120</b> N120 Extension Ring 20 II	<b>18809</b> 180mm Optical Glass Wide Angle Port			
	Tamron 17-28mm f/2.8 Di III RXD	<b>37157</b> STE1728-Z  <b>37157 + 37158</b> STE1728-Z + STE1728-F	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II	<b>22140</b> N120 Extension Ring 40 II	<b>85204</b> N120 WACP - 2  <b>18802</b> 8.5" Acrylic dome port  * <b>18809</b> 180mm Optical Glass Wide Angle Port  <b>18812</b> 230mm Optical Glass Wide Angle Port			Lens FOV 104-75° Converted FOV 123-89°

<sup>1</sup>. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.  
Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.  
Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance  
\* Secondary setup recommendation based on optical performance



## N100 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM ( Full Frame Format Lens )

	CAMERA LENS	GEAR	PORT ADAPTOR		PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
WIDE ANGLE FULL FRAME	Zeiss Batis 18mm F/2.8		<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II		<b>22120</b> N120 Extension Ring 20 II		<b>18809</b> 180mm Optical Glass Wide Angle Port	
	Sony FE 28mm f/2 + Sony 21mm Ultra-Wide Conversion Lens		<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II		<b>22130</b> N120 Extension Ring 30 II		<b>18809</b> 180mm Optical Glass Wide Angle Port	
	Sony FE 28mm f/2 + Sony 16mm Fisheye Conversion Lens		<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II		<b>22130</b> N120 Extension Ring 30 II		<b>18810</b> 140mm Optical Glass Wide Angle Port	
	Sony Full Frame Camera Sensor	<b>36317</b> Filter Holder				<b>37202</b> Nikonos Adaptor	<ul style="list-style-type: none"> <li>U/W Nikkor 15 mm f/2.8</li> <li>U/W Nikkor 20 mm f/2.8</li> <li>U/W Nikkor 80mm f/1.4</li> <li>Sea &amp; Sea 12mm f/3.5 Fisheye for Nikonos</li> </ul>	
CANON EF-MOUNT	Sigma 15mm F2.8 EX DG Diagonal Fisheye with Metabones T Smart Adaptor III/IV/V	<b>19546</b> SC15-F	<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II				<b>18810</b> 140mm Optical Glass Fisheye Port	
	Other Canon EF-mount Lenses with Metabones T Smart Adaptor III/IV/V		<sup>1</sup> <b>37305</b> N100 to N120 35.5mm Port Adaptor II				<b>N120 Canon EF-Mount Port System</b>	

1. # 37305 can be used on all Sony A series housings. #37303 can also be used on NA-A7RII, NA-A7RIII and NA-A9 housings.  
 Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.  
 Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended port system based on best optical performance  
 \* Secondary setup recommendation based on optical performance